PLANER/MOULDERS Models



Logosol PH360



Logosol PH365



Logosol PH260



Logosol PH260 ECO



Logosol DH410



Logosol SH410

Weight	600 kg	925 kg	350 kg	350 kg	225 kg	195 kg
Electrical system	16.25 kW	19.25 kW	13.2 kW	12.2 kW	6.2 kW	3.2 kW
Electrical connection	3-phase, 400 V, 32 A	3-phase, 400 V, 32 A	3-phase, 400 V, 16 A	3-phase, 400 V, 16 A	3-phase, 400 V, 16 A	3-phase, 400 V, 16 A
Feed	Standard: 3-15 m/min	Standard: 3-15 m/min	Standard: 2-12 m/min	Standard: 5m/min	Standard: 5 m/min	Standard: 5 m/min
Plane down to	8 mm	8 mm	8 mm	8 mm	8 mm	6 mm (utan anhåll)
Max. material width	360 mm	360 mm	260 mm	260 mm	410 mm	410 mm
Capacity						
4-sided machining width/height	360/10 to 130 mm	360/10 to 130 mm	15 till 260/10 to 100 mm	15 till 260/10 to 100 mm	–	–
2-sided machining width/height	410/10 to 230 mm	410/10 to 230 mm	300/10 to 230 mm	300/10 to 230 mm	325/100 mm	–
Planing width/height	510/10 to 230 mm	510/10 to 230 mm	410/10 to 230 mm	410/10 to 230 mm	410/10 to 250 mm	410/ 10 to 250 mm
Resawing height/sawblade diameter	–	–	–	–	–	80/180
Top cutter						
Diameter	88 mm	88 mm	72 mm	72 mm	72 mm	72 mm
Width	510 mm	510 mm	410 mm	410 mm	410 mm	410 mm
Motor power	5.5 kW	5.5 kW	4 kW	3 kW	3 kW/ 4 kW	3 kW/ 4 kW
Take-off, planing	0-8 mm	0-8 mm	0-8 mm	0-8 mm	0-8 mm	0-8 mm
Max. profile depth	20 mm	20 mm	20 mm	20 mm	20 mm	20 mm
Bottom cutter						
Diameter	72 mm	72 mm	72 mm	72 mm	–	–
Width	410 mm	410 mm	300 mm	300 mm	–	–
Motor power	4 kW	4 kW	3 kW	3 kW	–	–
Take-off, planing	0-8 mm	0-8 mm	0-4 mm	0-4 mm	–	–
Take-off, moulding	Max. 10 mm	Max. 10 mm	Max. 10 mm	Max. 10 mm	–	–
Side cutter						
Spindle diameter	30 mm	30 mm	30 mm	30 mm	30 mm	–
Max. cutter height	130 mm	130 mm	100 mm	100 mm	100 mm	–
Max. diameter	140 mm	140 mm	140 mm	140 mm	140 mm	–
Motor power	3 kW	3 kW	3 kW	3 kW	3 kW	–
5th cutter						
Spindle, standard	–	30 mm	–	–	–	–
Spindle for endmills	–	1-20 mm	–	–	–	–
Motor power	–	3 kW	–	–	–	–